



2 Carlton Avenue, East Rutherford, New Jersey 07073

Phone: (201) 935-8561
www.mil-comm.com

Fax: (201) 935-6059
sales@mil-comm.com



Extended Life, Extreme Duty Heavy Grease

- Superior quality, multi-grade lubricant
- High-temperature performance
- Low-temperature dependability
- Ultra-extreme pressure protection
- Excellent anti-wear capabilities, even under high load and severe shock
- Superior protection against water and corrosion

Ideal for gears, bearings, couplings, chassis, wheels, etc.

For use in general industrial, marine, automotive, and farm applications

Exceeds all NLGI GC-LB, ASTM Test Standards
(NLGI #2; Soap Type = Lithium-complex)

ASTM Test	Property	Value
D1264	Water Resistance @ 80°C	996
D1743	Rust Protection, Rating	Pass
D2266	Wear Protection Scar Diameter	0.49 mm
D2509	Load Carrying Properties (PSI)	150+ lbs
D2596	EP Performance: Load Wear Index	55 kgf
	Weld Point	350 kgf
D3336	Lube-life: 10,000 rpm @ 325°F	210 hrs
D3527	High Temperature Life	140 hrs
D4170	Fretting Protection (Mass Loss)	4.5 mg
D4289	Elastomer CR Compatibility: Volume Change	+22%
	Hardness Change (Durometer - A pts.)	-7%
D4290	Leakage Tendencies	7g
D4693	Low-Temperature Performance @ -40°C	14 Nm